



**L7641**

**Product Features:**

- **Exterior:** 2.4-oz, 100% nylon dobby check
- **Interior:** 100% polyester plush fleece
- Raglan sleeves
- Polyester/spandex binding on cuffs and hood
- Longer hem in back for extra coverage

Ladies' sizes: XS-4XL

**Icons/Fabric Features:**



**Available Colours and PMS Colours**

*Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference*

BLACK



Black 6C

ASPHALT



432C

VERY BERRY



512C

Due to the nature of nylon, special care must be taken throughout the decoration process.

## L7641- COAL HARBOUR® Kasey Plush Lined Shell Ladies' Jacket

### GARMENT MEASUREMENTS

Size	XS	S	M	L	XL	2XL	3XL	4XL
<b>Chest - Half Measure</b>	18"	19 1/2"	21"	22 1/2"	24"	25 1/2"	27 1/2"	29 1/2"
<b>Chest - Full Measure</b>	36"	39"	42"	45"	48"	51"	55"	59"
<b>Body Length from HPS (At Front)</b>	25"	25 1/2"	26"	26 1/2"	27 1/2"	28 1/2"	29"	29 1/2"
<b>Body Length from HPS (At Back)</b>	26"	26 1/2"	27"	27 1/2"	28 1/2"	29 1/2"	30"	30 1/2"
<b>Sleeve Length-CB</b>	29"	31"	33"	34"	35"	35 1/2"	36"	36 1/2"

*Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurement instructions.*

### LADIES' General Sizing Guide

Size	XS	S	M	L	XL	2XL	3XL	4XL
<b>Numeric Size</b>	2	4-6	8-10	12-14	16	18-20	22	24
<b>Bust</b>	32"-34"	35"-36"	37"-38"	39"-41"	42"-44"	45"-47"	48"-51"	52"-55"
<b>Waist</b>	24"-25"	26"-27"	28"-30"	30"-32"	33"-35"	36"-38"	40"-42"	42"-44"
<b>Hip</b>	33"-35"	35"-37"	37"-39"	39"-41"	42"-44"	45"-47"	48"-50"	50"-52"
<b>Sleeve Length-CB</b>	30"-30 1/2"	30 1/2"-31"	31 1/2"-32"	32 1/2"-33"	33 1/2"-34"	34"-34 1/2"	34 1/2"-35"	34 1/2"-35"

COAL HARBOUR®

### PRINTING INSTRUCTIONS FOR NYLON FABRICS

**Due to the nature of Nylon fabric, special care must be taken throughout the decoration process. Special care must be taken during the decoration process and after.**

Here are some tips to effectively decorate these products.

#### Heat Transfer/Screen Printing:

- Garment temperature must not exceed 310°F or 154°C.
- Use fast fashion/low cure temperature ink to help prevent the need for a higher temperature to cure the ink.
- A test sample run is recommended in all printing processes, especially if you have a large order or if your printer does not specialize in