

Essential Puffy Ladies' Jacket

DF7612L

Product Features:

- **Exterior:** 3.5-oz, 100% DWR nylon taffeta with matte finish
- **Fill:** 12.3-oz, 100% polyester micro down
- **Lining:** 100% polyester taffeta
- PFAS free water repellent fabric treatment

Ladies' sizes: XS-3XL




Contoured Fit



Full length inner storm flap with chin guard

Embroidery access



Binding at sleeve opening

Exposed pockets with reverse coil zippers

Available Colours and PMS Colours

Textile fabric colours are subject to dye lot variation and will not be exact match to print pantone reference



BLACK
426C

DF7612L - DryFrame® Essential Puffy Ladies' Jacket

Garment Measurements

Size	XS	S	M	L	XL	2XL	3XL
Chest - Half Measure	19"	20"	21"	22 1/2"	24"	25 1/2"	27 1/2"
Chest - Full Measure	38"	40"	43"	45"	48"	51"	55"
Body Length from HPS	25"	25 1/2"	26"	27"	28"	29"	29 1/2"
Sleeve Length - CB	32 1/2"	33 1/4"	34"	34 3/4"	35 1/2"	36 1/4"	37"

Finished measurements in inches. Refer to "How to Measure" guide for detailed information on measurements instructions.

Ladies' General Sizing Guide

Size	XS	S	M	L	XL	2XL	3XL
Numeric Size	2	4-6	8-10	12-14	16	18-20	22
Bust	32"-34"	35"-36"	37"-38"	39"-41"	42"-44"	45"-47"	48"-51"
Waist	24"-25"	26"-27"	28"-30"	30"-32"	33"-35"	36"-38"	40"-42"
Hip	33"-35"	35"-37"	37"-39"	39"-41"	42"-44"	45"-47"	48"-50"
Sleeve Length-CB	30"-30 1/2"	30 1/2"-31"	31 1/2"-32"	32 1/2"-33"	33 1/2"-34"	34"-34 1/2"	34 1/2"-35"

Printing Instructions

Due to the nature of Nylon fabric, special care must be taken throughout the decoration process. Here are some tips to effectively decorate our performance products.

- Garment temperature must not exceed 290°F or 143°C. Exceeding this temperature will cause the fabric to shrink, become wavy or cause dye migration.
- Dryer temperature and belt speeds must be changed accordingly for nylon fabric.
- If flashing these garments, do not exceed 1-2 seconds. Anything longer may damage the fabric as stated above.

EMBROIDERY: Embroidery is recommended for this garment. An embroidery access zipper is included in the inside liner

SCREEN PRINTING/HEAT TRANSFERS:

- Garment temperature must not exceed 250-290°F or 120-155°C.
- Use fast fushion/low cure temperature ink to help prevent the need for a higher temperature to cure the ink.

A test sample run is recommended, especially if you have a large order or if your printer does not specialize in printing on nylon fabric.